



**Requires lens purchase**  
(Choose from 4 available options)

**EPSON®**  
EXCEED YOUR VISION

# Epson PowerLite® 7900p

Made to shine in any setting, and manage from anywhere on the network

With 4000 ANSI lumens and convenient network monitoring and control, the Epson PowerLite 7900p provides remarkable power and performance. XGA resolution, a 700:1 contrast ratio, and Epson LCDs work with its incredible brightness to ensure superior image quality, while EasyManagement™ technology facilitates easy remote operation.

For added flexibility, this whisper-quiet (36db/33db) projector includes five computer/video connections, plus three lens options. Its expansive feature set also includes +/- 40° advanced keystone correction, and password-protected security features.

Ideal for large classrooms or conference rooms, the Epson PowerLite 7900p offers the perfect combination of power and versatility. IS personnel will appreciate its remote management and maintenance features, while presenters will enjoy its incredible quality and performance.

**Ultra bright 4000 ANSI lumens, weighs only 12.3 lb**

- Remarkable brightness that's ideal for large classrooms or conference rooms

**Convenient networking capability with EasyManagement technology**

- Built-in remote access—turn the projector on and off remotely
- Centralized monitoring, maintenance and control over the LAN
- Provides real-time information (source status, power status, and more), via:
  - EMP Monitor software utility (included)
  - Web browser—no special software required!
  - SNMP (Simple Network Management Protocol)
  - E-mail notification, via SMTP, to notify users of issues related to the temperature, fan, and lamp
- Enables secure access via password-protection features
- Works with the projector's built-in Ethernet connection

**Superior detail and razor-sharp contrast**

- Three Epson LCDs for accurate colors, and rich color saturation evenly distributed color across the screen
- XGA (1024 x 768) resolution for sharp, vivid detail
- 700:1 contrast ratio for outstanding image detail



**Easy installation, setup and operation**

- Image corrections tools for flexible setup and installation
  - 40° vertical keystone correction
  - QuickCorner™ for easy screen/image alignment
  - WallShot™ for color correction on a colored wall
- 1.35x zoom with optional lenses for positioning flexibility
- Preview function with seven convenient SnapWindows™
- Monitor out capability for simultaneous viewing on a monitor

- Easy-to-use control panel
  - Manage the setup and installation process, zoom lens, picture-in-picture capability, focus controls, and more
  - Operate multiple projectors simultaneously
- Brightness control function accommodates various lighting conditions and room sizes, and can extend the lamp life for more cost-effective operation (3000 hours in Low Brightness mode, 2000 hours in High Brightness mode)
- Five inputs including D-Sub15, BNC, DVI, S-Video, and Video
- Search function automatically recognizes and displays connected inputs, and switches instantly between them
- RGB auto detect
- Direct Power On turns on the projector with one system switch
- Whisper-quiet operation (36db/33db) ensures the presentation is the center of attention (silent when in AV Mute mode)
- Password-protected security features, plus operation lock, prevents unauthorized setting manipulation

**Outstanding Epson service and support (two-year limited warranty)**

- 90-day lamp warranty for added dependability
- Epson Road Service program provides a replacement projector, typically within 24 hours
- Epson PrivateLine™ dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday – Friday (Calls are answered live, typically in about a minute.)
- International warranty in over 45 countries



# Epson PowerLite 7900p Specifications

<b>Projection System</b>	Epson original LCD technology	
<b>Projection Method</b>	Front/rear/ceiling mount	
<b>LCD</b>		
Driving method	Epson Poly-silicon TFT Active Matrix	
Pixel number	786,432 pixels x 3 (1024 x 768) LCDs	
Native resolution	XGA	
Aspect ratio	4:3 (supports 16:9; 5:4)	
Pixel arrangement	Stripe	
<b>Projection Lens</b>		
Type	Manual zoom/focus	
F-number	1.7 to 2.3	
f-number	28 to 37mm	
Zoom ratio	1.0:1.35	
<b>Lamp</b>		
Type	250W UHE	
Life*	2000 (High Brightness), 3000 (Low Brightness)	
<b>Screen Width Ratio: (Distance/Width)</b>	1.32 to 1.8:1	
<b>Screen Size (Projected Distance)</b>	30" to 300" (2.6' to 36.1')	
<b>Keystone Correction</b>	Vertical: ±40 degrees, Horizontal: ±20 degrees Auto Keystone Correction (Vertical only)	
<b>Brightness (Typical)</b>	4000 ANSI lumens (High Brightness) 3000 ANSI lumens (Low Brightness)	
<b>Contrast Ratio</b>	700:1	
<b>Brightness Uniformity (Typical)</b>	90%	
<b>Color Reproduction</b>	24 bit; 16.7 mil	
<b>Audio Output</b>	5W Monaural	
<b>Operating Temperature</b>	41°F to 95°F (5°C to 35°C)	
<b>Power Supply Voltage</b>	100-120V/200-240V ±10%, 50/60Hz AC	
<b>Power Consumption</b>	350W, 47W at sleep mode: Network ON 1.5W at sleep mode: Network OFF	
<b>Dimensions</b>	12.8" x 16.5" x 4.6"	
<b>Weight</b>	12.3 lb/5.6kg	
<b>Fan Noise</b>	36db (High Brightness), 33db (Low Brightness)	
<b>Effective Scanning Frequency Range</b>		
<i>Analog</i>		
Pixel Clock	13.5MHz to 230MHz	
Horizontal	15KHz to 107KHz	
Vertical	50Hz to 120Hz	
<i>Digital</i>		
Pixel Clock	25MHz to 135MHz	
Horizontal	15KHz to 80KHz	
Vertical	50Hz to 85Hz	
<b>Remote Control Features</b>		
Features	Keystone, brightness, source selection, power, PinP, preview, page up/page down, color mode, volume, presets, e-zoom, a/v mute, freeze, effects	
Operating angle	Right/Left ± 30 degrees Upper/Lower ± 15 degrees	
Operating distance	33 ft (10m)	
<b>RGB</b>	<b>Analog RGB I/O</b>	<b>Digital RGB Input</b>
Display performance		
Native	1024 x 768	1024 x 768
Resize	1600 x 1200 1280 x 1024 800 x 600 640 x 480	1280 x 1024 800 x 600 640 x 480
Input terminal		
Video	Mini D-sub 15 pin x 1 5-BNC x 1	DVI Type D x1
Audio	Stereo mini jack (for Mini D-sub), RCA x 2 (for 5BNC)	Stereo mini jack

\*Lamp life results will vary depending upon mode selected, environmental conditions, and usage.

**EPSON®**  
EXCEED YOUR VISION

**Epson America, Inc.**  
3840 Kilroy Airport Way, Long Beach, CA 90806

**Epson Canada, Ltd.**  
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Specifications and terms are subject to change without notice. Epson is a registered trademark and EasyManagement, SnapWindows, WallShot, QuickCorner and 3 LCD are trademarks of Seiko Epson Corporation. PowerLite is a registered trademark and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2005 Epson America, Inc. CPD-18755R1 7/05 PDF

<b>RGB (cont.)</b>	<b>Analog RGB I/O</b>
Output terminal	
Video	Mini D-sub 15pin (monitor out) x1
Audio	Stereo mini jack
<b>Video I/O</b>	
Display performance	NTSC: 525 line PAL: 525 line (Depends on observation of the multi burst pattern)
Input signal	NTSC/NTSC4.43/PAL/M-PAL/ N-PAL/PAL60/SECAM HDTV: 480i, 480p, 720p, 1080i
Input terminal	
Video	Composite video: RCA(Yellow) x 1 S-Video: Mini DIN Component video: Mini D-sub 15pin (in common with Analog RGB connector) Video-RGB: Mini D-sub 15pin (in common with Analog RGB connector)
Audio	RCA(White/Red) x 2
Audio signal	500m Vrms/47Kohm
<b>Control I/O</b>	
USB I/O	USB connector series B x 1 (for mouse, keyboard)
Serial I/O	Mini D-sub 9pin x 1 RS-232C RJ45 x 1
Network interface	
<b>Security</b>	Kensington®-style lock provision
<b>Warranty</b>	Two-year limited warranty, two-year international warranty, 90-day lamp warranty, Epson Road Service Program and Epson PrivateLine dedicated toll-free support (U.S. and Canada only)
<b>Supplied Accessories</b>	Power cable, remote control, 2 AA batteries, computer cable, USB cable, CD-Rom (Windows-based EasyManagement software), Start Here Kit.
<b>Product/Accessory Part Numbers</b>	
Epson PowerLite 7900p projector	V11H170920
<b>Lens must be selected at time of purchase:</b>	
Standard lens	V12H004M03
Wide throw zoom lens	V12H004W03
Long throw zoom lens	V12H004L05
Replacement lamp	V13H010L22
Air filter set	V13H134A01
Remote control cable set	V12H005C28
Digital video cable DVI to DVI, 3m	ELPKC20
Digital video cable DVI to DFP, 3m	ELPKC21
S-video cable	ELPSV01
Component video cable	ELPKC19
Ceiling mount	ELPMB40
Suspension adapter	ELPMBAPL
False ceiling plate	ELPMBFCP
Security bracket/cabing for gyro lock mounts	ELPMBSEC
Adjustable ceiling channel	ELPMBACC
Distribution amplifier	ELPDA01
Mac adapter set	ELPAP01
ATA shipping case	ELPKS46
ATA molded hardshell case	ELPKS48
50" portable screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
83.6" hanging pull-down screen	ELPSC09
Kensington security lock	ELPSL01
High resolution document imager (ELPDC05)	V12H162020
High resolution document camera (ELPDC04)	V12H064020
<b>Support—The Epson Connection<sup>SM</sup></b>	
Pre-Sales Support U.S. and Canada	800-463-7766
Automated Technical Support	800-922-8911
Internet Web Site	www.epson.com
<b>Presenters ONLINE<sup>SM</sup></b>	presentersonline.com

